

# Rhodes

TRAILERS & TRUCK BODIES

## Series APT Aluminum Platform Trailer



Tool boxes, side kits, cargo tie downs, coil package, LED lights, suspension options...



Removable bulkhead ?



21" deep two-piece main beam



? Steps, lights, closure plate



[www.rhodestrailers.com](http://www.rhodestrailers.com)

# Rhodes



# Specifications

## Series – APT Aluminum Platform Trailer

### STANDARD FEATURES

#### **BASE TRAILER**

LENGTH 40'-0" to 53'-0"  
WIDTH 96" & 102" with or without rubrail & stake pockets  
MAIN BEAM 21" deep, 2-piece 6061-T6  
FRONT CORNERS Square or 45 degree  
DECK HEIGHT 53" rear, 61" front  
BULKHEAD Optional - removable or stationary

#### **DECK**

FLOOR 1-1/4" thick hollow core 6061-T6  
WOOD NAILERS (2) Apitong center of beam (1) outside of beam each side  
CROSSMEMBERS 5" channel – 18" on center spacing (15" optional)  
OUTER SIDE RAILS 6-1/2" deep 6061-T6  
STAKE POCKETS 24-1/8" on center both sides external & rear internal  
RUB RAILS Both sides & rear  
PIPE SPOOL SPACERS (2) between each stake pocket  
SLIDING TIE DOWNS Optional 2, 4 or 6 full length integral deck track  
COIL PACKAGE Optional  
CHAIN TIE DOWNS Optional  
CHAIN TIE DOWNS Optional  
WINCHES & TIE DOWNS Optional

#### **RUNNING GEAR**

SUSPENSION Hendrickson Intraxx 250-17, 50,000 lb. capacity  
REAR DICHARGE VALVE Optional  
AXLES (2) integral 5" round, 77-1/2" track, tapered spindles  
AXLE SPACING / SETTING 122" spread, 30" center rear axle to end deck  
BRAKES FMVSS-121, 16-1/2" x7" XEM 'S'-cam, Meritor-WABCO 4S/2M anti-lock 30/30 chambers,  
HUBS / DRUMS Outboard mount hub piloted 10 stud Walther, Centrifuse drums  
Stemco Platinum series bearings, seals & aluminum hub caps  
Optional aluminum hubs  
WHEELS (8) 24.5 x 8.25 steel- Optional Aluminum wheels  
TIRES (8) 11R24.5 Michelin XTE-2, load rating G

#### **COMPONENTS**

LIGHTS FMVSS-108 - (5) Markers each side, Mid turn in aluminum boxes, (3) 4" round Stop, tail, turn in rear boxed crossmember, (3) center ID, all LED, license lamp

ELECTRICAL 12-volt, 7-way harness

ISO CABLE Optional  
KINGPIN & COUPLER 36" setting, 5/16" thick steel HSLA, bolt-on, 2" SAE kingpin  
Optional aluminum coupler w/poly plate; 24", 30" and 42" settings

TIRE CARRIER Optional  
LANDING GEAR Holland 2-speed with sand shoes  
DOCK BUMPERS (1) rubber each corner rear  
BUMPER, REAR Tubular, 96" wide, NON-underride (FMVSS223/224 Optional)

BUMPER CLOSURE Optional  
STEPS & LADDERS Optional  
SPLASH GUARDS, FRONT 24"x 24" in front of both axles  
MUD FLAPS, REAR 24"x 40" behind both axles

#### **ACCESSORIES**

STORAGE BOX Optional  
SIDE KIT Optional

#### **FINISH DETAILS**

FINISH / BODY Natural aluminum, steel parts painted black polyurethane  
STRIPING Color choice



**the Truck & Trailer Store**

1054 Dukes Road Turbeville, SC 29162 Ph: 843-659-9959 Fax: 843-659-9957

[www.rhodestrailers.com](http://www.rhodestrailers.com)