

Rhodes

TRAILERS & TRUCK BODIES



RSS Series

All-Steel with AR450 body construction with optional High-Lift tailgate, tarp & graphics



High-Lift Air Tailgate



Elliptical design reduces weight for maximum legal payload



Rhodes RSS

Specifications

CHASSIS – RUNNING GEAR

LENGTH	22'-0" – 28'-0"
MATERIAL	Steel WF beam or fabricated 20" deep beam
KINGPIN & COUPLER	2" SAE bolt-in kingpin or weld-in w/3/8" thick steel coupler plate
LANDING GEAR	Single, <u>Holland</u> Mark V, two speed 200,000 lb. static capacity
TIRE CARRIER	Optional
SUSPENSION	Reyco 21-B cast iron w/ AR450 wear pads, single leaf springs
LIFT AXLES	Optional
AXLES	Meritor, 5" round, 71.5" or 77.5" track, straight or tapered spindles Stemco Platinum oil seals w/Pro-Torque nut
BRAKES	FMVSS-121 WABCO Meritor ABS 2S/1M ; 16-1/2"x 7"x 3/4" S-cam air 30/30 chambers all axles; Dust shields; Automatic slack adjusters
ELECTRICAL	12-volt neg. ground 7-way harness
HUBS / DRUMS	Outboard mount HD cast iron, hub piloted with cast drums
WHEELS	22.5 x 8.25 steel disc 10 stud, hub-piloted (white)
TIRES	11R22.5 Michelin XZE 14PR , Load Range 'G'
FINISH	Primed & painted STD acrylic enamel

BODY

LENGTH	22'-0" – 28'-0" Steel Radius 'U' shape
OUTSIDE WIDTH	96"
SIDE HEIGHT	54"
BULKHEAD	Slope forward design
CAPACITY	25 – 33 cubic yards
HOIST	Custom front telescopic; jumper hose w/push/pull coupler
SIDE MATERIAL GA.	1/4" AR450 Hardox
BULKHEAD MATERIAL GA.	1/4" AR450 Hardox
VERTICAL SIDE BRACES	Front & rear corners (center intermediate optional)
RUBRAILS	4" tubing top; NO Bottom
SIDEBOARDS / CAP ANGLE	Inverted cap angle
STEPS & LADDERS	Driver side front in & out & rear panel out only
LIGHTS	FMVSS-108 (3)Markers each side bottom only; Mdl. 60 oval rear posts; (3)stop/tail/turn each side & (3)center ID in rear body crossmember; (1)License
FLOOR MATERIAL GA	1/4" AR450 Hardox
CROSSMEMBERS	4" x 4" boxed tubing 18" or 15" on center spacing
TAILGATE	1/4" thick AR450 Hardox plate; 54" Ht.; Spring/Air chamber lock with frame control and gladhand to front; 6", 12" or 24" slope;
LIGHTGUARD APRON	3/8" thick x 4" long x full width, rear
BODY HOLD DOWNS	One pair, spring loaded
FENDERS	Full length each side 30 degree angle over tubing frame
SPLASH GUARDS FRONT	14"x24" alum w/ 12"x24" front of tire; 12"x24" rubber on front corner fenders
MUD FLAPS REAR	(2)24"x42" rubber mtd on angled brackets (1)full rubber center frame (all across rear)
FINISH / BODY	Primed & painted STD acrylic enamel



the Truck & Trailer Store
1054 Dukes Road Turbeville, SC 29162 Ph: 843-659-9959 Fax: 843-659-9957

www.rhodestrailers.com